



THE WEST BENGAL POWER DEVELOPMENT CORPORATION LIMITED
(A Govt. of West Bengal Enterprise)
Bakreswar Thermal Power Project
P.O.Bk.T.P.P , Dist -Birbhum,Pin -731104

NIT No.:WBPDC/Tend-Adv/CC/13-14/132/BkTPP

Date: 02.11.2013

Sealed tenders in two parts, Part A (for technical specification bid) and Part B (for commercial price bid) in duplicate are invited by the General Manager, BkTPP with same material specification for the supply of following material at BkTPP.

1. Description of Materials : As per Annexure-I
2. Estimated Cost : Rs. 44,17,000/-
3. Earnest Money : Rs. 90,000/-
4. Cost of Tender Paper : Rs. 1,000/-
5. Sale of Tender Paper : 04.11.2013 to 22.11.2013
6. Pre-bid discussion : 26.11.2013 at 11.00 A.M.
7. Last Date of Submission of Sealed Tender Paper : 03.12.2013 up to 02.00 P.M.
8. Opening of Tender
- 8a. Part-A (for technical bid) : 03.12.2013 at 03:00 P.M.
- 8b. Part-B (for price bid) : Opening date will be intimated to the successful i.e. technically accepted bidders later on.
- 9a. Material Delivery Period : Twelve (12) weeks from the date of the order.

[Qualifying Requirement:

1. Must be a manufacturer / distributor / dealer of the items.
2. Documents to prove the experience of the tenderers in successful execution of Purchase Order in the last five financial years they should submit Purchase Order copies for i) amount of Rs.10,00,000/- or above in single order / ii) amount of Rs.7,00,000/- each or above in two orders / iii) amount of Rs.5,00,000/- each or above in three orders. And End user's certificate or Material Receipt Note Voucher is to be submitted as supporting document for proof of execution of above Purchase Order/s.]

Detailed terms & conditions are set forth in the Tender Paper (Non - Transferable) which can be obtained from the Sr. Manager(S&P), BkTPP on application. The cost of Tender Paper is to be deposited in the Account Section, BkTPP from 10.30 AM to 01.30 PM (except Saturday, Sunday and Holiday). Tender Paper will not be issued against DD / MO / Cheque and by post. If any change or extension of due date or any corrigendum, may please visit website. The WBPDC reserves the right to accept or to reject any or all tender either in full or in part or to split up, if necessary without assigning any reasons whatsoever. For qualifying requirements and other details visit website www.wbpdcl.co.in

T. K. BOSE
SR.MGR(S & P)
BkTPP/WBPDC

ANNEXURE-I

SL NO	Item Code	Item Description	Unit	Required Quantity
1	06C010087	Cable, Copper, 0.5 Sq.mm Dia, 4 Pair, Screened, Armoured 600 Volt grade, 85 Deg.C rating, Stranded copper conductor, HR PVC insulation, Colour coded, Twisted to form a pair, Pairs twisted to fom a unit, Units laid up. Myler taped binding, overall screened with alluminised myler tape with tinned copper drain wire, extruded HR PVC inner sheath(IS:5831), galvanized steel round wire/strip armoured, extruded FRLS PVC overall sheath. Halogen free.	Mtr.	7500.00
2	06C010007	Cable, Copper, 0.5 Sq.mm Dia, 6 Pair, Screened, Armoured 600 Volt grade, 85 Deg.C rating, Stranded copper conductor, HR PVC insulation, Colour coded, Twisted to form a pair, Pairs twisted to fom a unit, Units laid up. Myler taped binding, overall screened with alluminised myler tape with tinned copper drain wire, extruded HR PVC inner sheath(IS:5831), galvanized steel round wire/strip armoured, extruded FRLS PVC overall sheath. Halogen free.	Mtr.	8000.00
3	06C010002	Cable, Copper, 0.5 Sq.mm Dia, 12 Pair, Screened Armoured. 600 Volt grade, 85 Deg.C rating, Stranded copper conductor, HR PVC insulation, Colour coded, Twisted to form a pair, Pairs twisted to fom a unit, Units laid up. Myler taped binding, overall screened with alluminised myler tape with tinned copper drain wire, extruded HR PVC inner sheath(IS:5831), galvanized steel round wire/strip armoured, extruded FRLS PVC overall sheath. Halogen free.	Mtr.	6000.00
4	06C010051	Cable, Single Core 1.5 Sq.Mm Cu Flexible PVC Insulated, Grey Colour 600V Grade, FRLS, Halogen free.	Mtr.	2000.00
5	06C010034	Cable, Copper, 0.5 Sq.mm Dia, 24 Pair, Screened Armoured. 600 Volt grade, 85 Deg.C rating, Stranded copper conductor, HR PVC insulation, Colour coded, Twisted to form a pair, Pairs twisted to fom a unit, Units laid up. Myler taped binding, overall screened with alluminised myler tape with tinned copper drain wire, extruded HR PVC inner sheath(IS:5831), galvanized steel round wire/strip armoured, extruded FRLS PVC overall sheath. Halogen free.	Mtr.	4000.00
6	06C010001	Cable, Copper, 1.5 Sq.mm Dia, 2 Pair, Screened Armoured. 600 V Grade, FRLS, Halogen free	Mtr.	2000.00
7	04C010029	Cable,LT,Control, Copper, PVC Insulated, Steel Armoured,1.1KV Grade, 3 Core X 2.5 Sqmm FRLS, Halogen free.	Mtr.	4000.00

Tolerance: 5% tolerance of each cable in total length.